



Schneider Electric USA
 1415 South Roselle Road
 Palatine, IL 60067
 Customer Care Center: 1-888-778-2733
 Web: www.schneider-electric.us

ITEM # XBTGT5230, HUMAN MACHINE INTERFACE XBTGT5230 PANELS

10.4" Graphic Touchscreen HMI



Specifications	
North America Certifications	UL 508, UL 1604, CSA C22-2 no. 14
IEC, CE Certifications	EN 61131-2, IEC 61000-6-2, CE
FCC & EMC	FCC (Class A), C-Tick
Hazardous Locations	Class 1 Div 2 T4A or T5 (UL and CSA), ATEX Zone 2/22
Marine Certifications	ABS, BV, DNV, GL, LR, RINA, RMRS, RRR
Other Certifications	ACA, GOST
Common Automation Protocols	Modbus, Uni-TE, Modbus TCP/IP, FIPWAY, FIPIO, Modbus Plus
Other Protocols	PacDrive, Siemens, Omron, Mitsubishi, Rockwell
Operating Temperature Range	0c to 50c
Storage Temperature Range	-20c to +60c
Relative Humidity	0 to 90% non condensing
Screen Type	4k Color STN
Resolution	640 x 480 pixels (VGA), 172 cd/m2
Interface Ports	SUB-D9 (RS 232C/RS 422/485 serial link), RJ45 (RS485)
Ethernet Ports	Ethernet IEEE 802.3 10/100 Base-T (RJ 45)

USB Ports	Type A (V1.1)
Input/Output	1 audio out, 1 discrete in, 3 discrete out
Enclosure Rating	IP65, NEMA 4X indoor
Processor	266 Mhz RISC
SRAM	512k
Storage	32M EPROM
Supply Voltage	24 VDC