

NEOZED fuse link 400 V gL/gG, Size D01, 16A, Folding box



Figure similar

Model	
Product brand name	SETRON
Product designation	NEOZED fuse link
Design of the product	With tin-coated contact caps
Product variations	Pack of 10
Design of the fuse link	NEOZED fuse link

General technical data	
Size of fuse system / acc. to DIN EN 60269-1	D01
Operating class of the fuse link	gG
Supply voltage	
• at AC / rated value	400 V
• at DC	250 V
Protection class IP	IP20, with connected conductors
Switching capacity current / acc. to IEC 60947-2 / rated value	50 kA

### Dissipation

Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.6 W
Current / at AC / rated value	16 A

#### Main circuit




Operating voltage / rated value	400 V
Operating current / rated value	16 A

#### Appearance

Color coding of the fuse link	Gray
Maximum short-circuit current breaking capacity (I <sub>cu</sub> ) / at AC / rated value	50 kA
Mounting position	Any, preferably vertical
Net weight	5 g
Ambient temperature <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	-5 °C 40 °C
Environmental category	Up to 45°C at 95 % rel. humidity

#### Certificates

Reference code <ul style="list-style-type: none"> <li>• acc. to DIN EN 61346-2</li> <li>• acc. to DIN EN 81346-2</li> </ul>	F F
---	--------

General Product Approval	Declaration of Conformity	Test Certificates
 ÖVE	 VDE	 EG-Konf.
		<a href="#">Special Test Certificate</a>
		<a href="#">Type Test Certificates/Test Report</a>
		<a href="#">Miscellaneous</a>

#### other

[Environmental Confirmations](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE2316>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5SE2316>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SE2316](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2316)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

