

ATV66D23N4

adjustable speed drive ATV-66D with heat sink -
18.5 kW - without EMC filter



Main

Range of product	Altivar 66
Product or component type	Variable speed drive

Complementary

Product destination	Asynchronous motors
[Us] rated supply voltage	380...460 V (- 10...10 %)
Supply frequency	50...60 Hz (- 5...5 %)
Network frequency	47.5...63 Hz
Network number of phases	3 phases
Motor power kW	18.5 kW at 380...460 V
Motor power hp	25 hp
Line current	44.7 A at 380 V 35.6 A at 460 V
Apparent power	23 kVA at 400 V
Continuous output current	33 A at 400 V
Output frequency	0...0.3 kHz
Nominal switching frequency	2.5 kHz
Switching frequency	0.5...4 kHz 8...16 kHz with current derating
Local signalling	1 graphic display terminal
Output voltage	400 V
Communication port protocol	Modbus
Physical interface	RS485 multidrop serial link
Transmission rate	9.6...19.2 kbauds
Height	415 mm
Width	234 mm
Depth	245 mm
Option card	Communication card for CANopen Communication card for Ethernet Communication card for Uni-Telway Communication card for AS-Interface Communication card for Profibus DP Communication card for Fipio Communication card for Modbus Plus

Environment

IP degree of protection	IP00
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-25...70 °C
Operating altitude	> 1000...2000 m (derate : 1 % per 100 m) <= 1000 m

ATV66D23N4 is replaced by:



Variable speed drives ATV71HD15N4

variable speed drive ATV71 - 15kW-20HP - 480V - EMC filter-graphic terminal

Qty 1

Reason for Substitution: End of life | Substitution date: 01 April 2005
