



EL4132 | 2-channel analog output terminal -10...+10 V, 16 bit

The EL4132 analog output terminal generates signals in the range between -10 and +10 V. The voltage is supplied to the process level with a resolution of 16 bits and is electrically isolated. The output channels of the EtherCAT Terminal have a common ground potential. The EL4132 combines two channels in one housing. The signal state of the EtherCAT Terminal is indicated by light emitting diodes.

Technical data	EL4132 ES4132
Connection technology	2-wire, single-ended
Number of outputs	2
Power supply	via the E-bus
Signal voltage	-10...+10 V
Distributed clocks	yes
Distributed clock precision	<< 1 μ s
Load	> 5 k Ω (short-circuit-proof)
Output error	< 0.1 % (relative to end value)
Resolution	16 bit (incl. sign)
Electrical isolation	500 V (E-bus/signal voltage)
Conversion time	~ 40 μ s
Current consumption power contacts	–
Current consumption E-bus	typ. 210 mA
Bit width in the process image	2 x 16 bit AO output
Special features	Watchdog parameterisable; user synchronisation can be activated.
Weight	approx. 55 g
Operating/storage temperature	-25...+60 °C/-40...+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 20/variable
Pluggable wiring	for all ESxxxx terminals
Approvals	CE, UL, Ex