

NEOZED fuse link 400 V gL/gG, Size D01, 10A, Folding box with tin-coated contact caps



Model	
Product brand name	SETRON
Product designation	NEOZED fuse link
Design of the product	With tin-coated contact caps
Product variations	Pack of 10
Design of the fuse link	NEOZED fuse link

General technical data	
Size of fuse system / acc. to DIN EN 60269-1	D01
Operating class of the fuse link	gG
Supply voltage	
• at AC / rated value	400 V
• at DC	250 V
Protection class IP	IP20, with connected conductors
Switching capacity current / acc. to IEC 60947-2 / rated value	50 kA

Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1 W

Current / at AC / rated value	10 A
-------------------------------	------

### Main circuit

Operating voltage / rated value	400 V
Operating current / rated value	10 A

### Appearance

Color coding of the fuse link	Red
Maximum short-circuit current breaking capacity (Icu) / at AC / rated value	50 kA
Mounting position	Any, preferably vertical
Net weight	6 g
Ambient temperature <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	-5 °C 40 °C
Environmental category	Up to 45°C at 95 % rel. humidity

### Certificates

Reference code <ul style="list-style-type: none"> <li>• acc. to DIN EN 61346-2</li> <li>• acc. to DIN EN 81346-2</li> </ul>	F F
---	--------

General Product Approval	Declaration of Conformity	Test Certificates
--------------------------	---------------------------	-------------------



ÖVE



VDE



EG-Konf.

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

[Miscellaneous](#)

### other

[Environmental Conformations](#)

### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE2310>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SE2310>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SE2310](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2310)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

<http://www.siemens.com/specifications>

