



## Main

Range	Acti 9
Product name	Acti 9 STI
Product or component type	Fuse-disconnector
Device short name	STI
Poles description	1P + N

## Complementary


[In] rated current	10 A 16 A 2 A 20 A 25 A 4 A 6 A
Fuse curve	AM GG
Fuse size	10.3 x 38 mm
[Ue] rated operational voltage	500 V AC
[Ui] rated insulation voltage	500 V AC 50/60 Hz
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	75 mm
Colour	White
Connections - terminals	Screw clamp terminals 1 cable(s) 0.75...10 mm <sup>2</sup> rigid Screw clamp terminals 2 cable(s) 0.75...4 mm <sup>2</sup> rigid Screw clamp terminals 1 cable(s) 0.5...6 mm <sup>2</sup> flexible Screw clamp terminals 2 cable(s) 0.5...6 mm <sup>2</sup> flexible

Wire stripping length	12 mm
Tightening torque	2 N.m

## Environment

Standards	IEC 60269-1/2 IEC EN 60947-3
IP degree of protection	IP20
Pollution degree	3
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...80 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0844 - Schneider Electric declaration of conformity  <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations