## Product datasheet Characteristics

### XZCC12FDM40B

female, M12, 4-pin, straight connector - cable gland Pg 7



Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Straight female connector M12, 4 pins
Collar material	Metal
Status LED	Without
Cable connection	Screw terminal / wire size <= 0.75 mm² / clamping capacity 36 mm

### Complementary

Cable gland type	Pg 7	
Cable connector fixing	Screw-on	
[Ue] rated operational voltage	125 V AC 150 V DC	
[In] rated current	3 A	
Enclosure material	Plastic	
Insulating resistance	> 1000 GΩ	
Contact resistance	<= 8000 μOhm	
Product weight	0.02 kg	

#### Environment

IP degree of protection	IP67	ئ -
Ambient air temperature for operation	-4085 °C	- 411

### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0726 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	


#### Contractual warranty

Warranty period	18 months	

# Product datasheet Dimensions Drawings

## XZCC12FDM40B

### **Dimensions**



## Product datasheet Connections and Schema

### XZCC12FDM40B

### Connections and Schemes

