Product data sheet Characteristics

XZCC12FCM40B

female, M12, 4-pin, elbowed connector - cable gland Pg 7



Main		
Accessory / separate part category	Cabling accessories	
Accessory / separate part type	Connector	
Electrical connection	Elbowed female connector M12, 4 pins	
Collar material	Metal	
Status LED	Without	

Complementary

Accessory / separate part category	Cabling accessories			
Accessory / separate part type	Connector			
Electrical connection	Elbowed female connector M12, 4 pins			
Collar material	Metal			
Status LED	Without			
Cable connection	Screw terminal / wire size <= 0.75 mm² / clamping capacity 36 mm			
Complementary				
Cable gland type	Pg 7			
Cable connector fixing	Screw-on			
Ue] rated operational voltage	125 V AC 150 V DC			
In] rated current	3 A			
Enclosure material	Plastic			
nsulating resistance	> 1000 GΩ			
Contact resistance	<= 8000 μOhm			
Product weight	0.02 kg			
Environment				
P degree of protection	IP67			
Ambient air temperature for operation	-4085 °C			
Offer Sustainability				
RoHS (date code: YYWW)	Compliant - since 0726 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity			
Contractual warranty				
Narranty period	18 months			

Environment

IP degree of protection	IP67	_;
Ambient air temperature for operation	-4085 °C	

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0726 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity


Contractual warranty

Warranty period	18 months	

Product data sheet Dimensions Drawings

XZCC12FCM40B

Dimensions



(1) Cable gland : no. 7 plastic (Pg 7)

Product data sheet Connections and Schema

XZCC12FCM40B

Connections and Schemes

