



### Main

|                           |  |
|---------------------------|--|
| Device application        | Distribution   |
| Range                     | Acti 9   |
| Product name              | Acti 9 iC60  |
| Product or component type | Miniature circuit-breaker  |
| Device short name         | IC60N  |
| Poles description         | 3P   |
| Number of protected poles | 3  |
| [In] rated current        | 3 A  |
| Network type              | DC<br>AC   |
| Trip unit technology      | Thermal-magnetic   |
| Curve code                | C  |
| Breaking capacity         | 6000 A Icn at 400 V AC 50/60 Hz conforming to EN/IEC 60898-1<br>50 kA Icu at 12...60 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>50 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>50 kA Icu at 100...133 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>50 kA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>25 kA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>10 kA Icu at <= 180 V DC conforming to EN/IEC 60947-2 |
| Utilisation category      | Category A conforming to EN 60947-2<br>Category A conforming to IEC 60947-2  |
| Suitability for isolation | Yes conforming to EN 60898-1<br>Yes conforming to EN 60947-2<br>Yes conforming to IEC 60898-1<br>Yes conforming to IEC 60947-2   |
| Standards                 | EN 60898-1<br>EN 60947-2<br>IEC 60898-1<br>IEC 60947-2   |
| Quality labels            | NF   |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Complementary

|  |  |
|--|--|
| Network frequency                                | 50/60 Hz   |
| Magnetic tripping limit                          | 8 x I <sub>n</sub> +/- 20 %  |
| [Ics] rated service breaking capacity            | 50 kA 100 % conforming to EN 60947-2 - 220...240 V AC 50/60 Hz<br>50 kA 100 % conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz<br>50 kA 100 % conforming to EN 60947-2 - 380...415 V AC 50/60 Hz<br>25 kA 100 % conforming to EN 60947-2 - 440 V AC 50/60 Hz<br>50 kA 100 % conforming to IEC 60947-2 - 380...415 V AC 50/60 Hz<br>25 kA 100 % conforming to IEC 60947-2 - 440 V AC 50/60 Hz<br>50 kA 100 % conforming to IEC 60947-2 - 12...133 V AC 50/60 Hz<br>50 kA 100 % conforming to EN 60947-2 - 12...133 V AC 50/60 Hz<br>6000 A 100 % conforming to EN 60898-1 - 400 V AC 50/60 Hz<br>6000 A 100 % conforming to IEC 60898-1 - 400 V AC 50/60 Hz<br>10 kA 100 % conforming to IEC 60947-2 - 125...180 V DC<br>10 kA 100 % conforming to EN 60947-2 - 125...180 V DC |
| Limitation class                                 | 3 conforming to EN 60898-1<br>3 conforming to IEC 60898-1  |
| [Ui] rated insulation voltage                    | 500 V AC 50/60 Hz conforming to EN 60947-2<br>500 V AC 50/60 Hz conforming to IEC 60947-2  |
| [Uimp] rated impulse withstand voltage           | 6 kV conforming to EN 60947-2<br>6 kV conforming to IEC 60947-2  |
| Contact position indicator                       | Yes  |
| Control type                                     | Toggle   |
| Local signalling                                 | Trip indicator   |
| Mounting mode                                    | Fixed  |
| Mounting support                                 | DIN rail   |
| Comb busbar and distribution block compatibility | Top or bottom: YES   |
| 9 mm pitches                                     | 6  |
| Height   | 85 mm  |
| Width  | 54 mm  |
| Depth  | 78.5 mm  |
| Net weight                                       | 0.375 kg   |
| Colour   | White  |
| Mechanical durability                            | 20000 cycles   |
| Electrical durability                            | 10000 cycles   |
| Connections - terminals                          | Single terminal (top or bottom) 1...25 mm <sup>2</sup> rigid<br>Single terminal (top or bottom) 1...16 mm <sup>2</sup> flexible  |
| Wire stripping length                            | 14 mm for top or bottom connection   |
| Tightening torque                                | 2 N.m top or bottom  |
| Earth-leakage protection                         | Separate block   |

## Environment

|                                       |   |
|---------------------------------------|---|
| IP degree of protection               | IP20 conforming to IEC 60529<br>IP20 conforming to EN 60529 |
| Pollution degree                      | 3 conforming to EN 60947-2<br>3 conforming to IEC 60947-2   |
| Overvoltage category                  | IV  |
| Tropicalisation                       | 2 conforming to IEC 60068-1                                 |
| Relative humidity                     | 95 % at 55 °C   |
| Operating altitude                    | 0...2000 m  |
| Ambient air temperature for operation | -35...70 °C   |
| Ambient air temperature for storage   | -40...85 °C   |

## Offer Sustainability

|                          |                       |
|--------------------------|-----------------------|
| Sustainable offer status | Green Premium product |
|--------------------------|-----------------------|

|                            |   |
|----------------------------|---|
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Under investigation   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | No need of specific recycling operations  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|