

Main

Range of product	Phaseo Economic
Product or component type	Safety and isolation transformer
Rated power in VA	250 VA
Input voltage	230 V AC phase to phase, terminal(s): L1-L2 230 V AC single phase, terminal(s): N-L1
Output voltage	24 V AC
Secondary winding	Single
Protective cover	Without
Ambient air temperature for operation	-20...40 °C

Complementary

Input voltage limits	207...253 V
Network frequency limits	47...63 Hz
Input voltage tolerance	+/- 15 V
Efficiency	89 %
Power dissipation in W	30.9 W
Voltage variation at nominal load	5.04 % at 230 V
Output sustained overvoltage	0,063 (no load, hot state)
Voltage drop at rated load	<= 6.25 %
No load losses	12.3 W
Short-circuit voltage	0,083
Output protection type	Against overload, protection technology: external Against overvoltage, protection technology: external Against short-circuits, protection technology: external
Connections - terminals	Screw type terminals for input ground connection, connection capacity: 1 x 2.5...1 x 4 mm ² AWG 14...AWG 11 Screw type terminals for input connection, connection capacity: 4 x 2.5...4 x 4 mm ² AWG 14...AWG 11 Screw type terminals for output connection, connection capacity: 2 x 2.5...2 x 4 mm ² AWG 14...AWG 11
Marking	CE
Fixing mode	By 4 screws, screw(s) Ø = 5 mm on horizontal panel with derating to 90 % By 4 screws, screw(s) Ø = 5 mm on vertical panel, operating position: horizontal By 4 screws, screw(s) Ø = 5 mm on vertical panel, operating position: vertical

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Operating altitude	3000 m
Electrical insulation class	Class B
Width	98 mm
Height	106 mm
Depth	105 mm
Product weight	3.54 kg


Environment

Product certifications	EAC
IP degree of protection	IP20
Environmental characteristic	EMC conforming to EN 62041 Safety conforming to EN 61558-1 Safety conforming to EN 61558-2-6
Ambient air temperature for storage	-40...80 °C
Relative humidity	0...95 % during operation
Overvoltage category	Class I conforming to VDE 0106-1
Dielectric strength	Between input and ground Between output and ground Between input and output

Contractual warranty

Warranty period	18 months
-----------------	-----------

Dimensions




Dimensions in mm

a	b	c	G	J	Ø
98	106	105	84	86	5.8


Dimensions in in.

a	b	c	G	J	Ø
3.86	4.17	4.13	3.31	3.39	0.23

Internal Scheme



Primary Voltage Wiring



Secondary Voltage Wiring

