



## Main

|                                    |   |
|------------------------------------|---|
| Range of product                   | Altivar 312   |
| Product or component type          | Variable speed drive  |
| Product destination                | Asynchronous motors   |
| Product specific application       | Simple machine  |
| Assembly style                     | With heat sink  |
| Component name                     | ATV312  |
| Motor power kW                     | 1.5 kW  |
| Motor power hp                     | 2 hp  |
| [Us] rated supply voltage          | 200...240 V (- 15...10 %)   |
| Supply frequency                   | 50...60 Hz (- 5...5 %)  |
| Network number of phases           | Single phase  |
| Line current                       | 13.3 A for 240 V<br>15.8 A for 200 V, 1 kA  |
| EMC filter                         | Integrated  |
| Apparent power                     | 3.2 kVA   |
| Maximum transient current          | 12 A for 60 s   |
| Power dissipation in W             | 90 W at nominal load  |
| Speed range                        | 1...50  |
| Asynchronous motor control profile | Factory set : constant torque<br>Sensorless flux vector control with PWM type motor control signal  |
| Electrical connection              | L1, L2, L3, U, V, W, PA, PB, PA+, PC/- terminal 5 mm <sup>2</sup> AWG 10<br>AI1, AI2, AI3, AOV, AOC, R1A, R1B, R1C, R2A, R2B, LI1...LI6 terminal 2.5 mm <sup>2</sup> AWG 14   |
| Supply                             | Internal supply for logic inputs at 19...30 V, <= 100 mA for overload and short-circuit protection<br>Internal supply for reference potentiometer (2.2 to 10 kOhm) at 10...10.8 V, <= 10 mA for overload and short-circuit protection |
| Communication port protocol        | CANopen<br>Modbus   |
| IP degree of protection            | IP20 on upper part without cover plate<br>IP21 on connection terminals<br>IP31 on upper part  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

IP41 on upper part

|             |   |
|-------------|---|
| Option card | CANopen daisy chain communication card<br>DeviceNet communication card<br>Fipio communication card<br>Modbus TCP communication card<br>Profibus DP communication card |
|-------------|---|

## Complementary

|                                     |  |
|-------------------------------------|--|
| Supply voltage limits               | 170...264 V  |
| Network frequency                   | 47.5...63 Hz   |
| Prospective line I <sub>sc</sub>    | 1 kA   |
| Continuous output current           | 8 A at 4 kHz   |
| Output frequency                    | 0...500 kHz  |
| Nominal switching frequency         | 4 kHz  |
| Switching frequency                 | 2...16 kHz adjustable  |
| Transient overtorque                | 170...200 % of nominal motor torque  |
| Braking torque                      | 100 % with braking resistor continuously<br>150 % without braking resistor<br>150 % with braking resistor for 60 s   |
| Regulation loop                     | Frequency PI regulator   |
| Motor slip compensation             | Adjustable<br>Automatic whatever the load<br>Suppressable  |
| Output voltage                      | <= power supply voltage  |
| Tightening torque                   | 1.2 N.m L1, L2, L3, U, V, W, PA, PB, PA+, PC-<br>0.6 N.m AI1, AI2, AI3, AOV, AOC, R1A, R1B, R1C, R2A, R2B, LI1...LI6   |
| Insulation                          | Electrical between power and control   |
| Analogue input number               | 3  |
| Analogue input type                 | AI1 configurable voltage 0...10 V, input voltage 30 V max, impedance 30000 Ohm<br>AI2 configurable voltage +/- 10 V, input voltage 30 V max, impedance 30000 Ohm<br>AI3 configurable current 0...20 mA, impedance 250 Ohm  |
| Sampling duration                   | AI1, AI2, AI3 8 ms for analog<br>LI1...LI6 4 ms for discrete   |
| Response time                       | AOV, AOC 8 ms for analog<br>R1A, R1B, R1C, R2A, R2B 8 ms for discrete  |
| Linearity error                     | +/- 0.2 % for output   |
| Analogue output number              | 1  |
| Analogue output type                | AOC configurable current 0...20 mA, impedance 800 Ohm, resolution 8 bits<br>AOV configurable voltage 0...10 V, impedance 470 Ohm, resolution 8 bits  |
| Discrete input logic                | (LI1...LI4) logic input not wired, < 13 V (state 1)<br>(LI1...LI6) negative logic (source), > 19 V (state 0)<br>(LI1...LI6) positive logic (source), < 5 V (state 0), > 11 V (state 1)   |
| Discrete output number              | 2  |
| Discrete output type                | (R1A, R1B, R1C) configurable relay logic 1 NO + 1 NC, electrical durability 100000 cycles<br>(R2A, R2B) configurable relay logic NC, electrical durability 100000 cycles   |
| Minimum switching current           | R1-R2 10 mA at 5 V DC  |
| Maximum switching current           | R1-R2 on inductive load, 2 A at 250 V AC, (cos phi = 0.4, and L/R = 7 ms)<br>R1-R2 on inductive load, 2 A at 30 V DC, (cos phi = 0.4, and L/R = 7 ms)<br>R1-R2 on resistive load, 5 A at 250 V AC, (cos phi = 1, and L/R = 0 ms)<br>R1-R2 on resistive load, 5 A at 30 V DC, (cos phi = 1, and L/R = 0 ms) |
| Discrete input number               | 6  |
| Discrete input type                 | (LI1...LI6) programmable, 24 V 0...100 mA with PLC, impedance 3500 Ohm   |
| Acceleration and deceleration ramps | Linear adjustable separately from 0.1 to 999.9 s<br>S, U or customized   |
| Braking to standstill               | By DC injection  |
| Protection type                     | Input phase breaks drive<br>Line supply overvoltage and undervoltage safety circuits drive<br>Line supply phase loss safety function, for three phases supply drive<br>Motor phase breaks drive<br>Overcurrent between output phases and earth (on power up only) drive<br>Overheating protection drive    |


Short-circuit between motor phases drive  
Thermal protection motor


|                       |  |
|-----------------------|--|
| Insulation resistance | >= 500 mOhm at 500 V DC for 1 minute   |
| Local signalling      | 1 LED red for drive voltage<br>Four 7-segment display units for CANopen bus status |
| Time constant         | 5 ms for reference change  |
| Frequency resolution  | Analog input 0.1...100 Hz<br>Display unit 0.1 Hz                                   |
| Connector type        | 1 RJ45 Modbus/CANopen  |
| Physical interface    | RS485 multidrop serial link  |
| Transmission frame    | RTU  |
| Transmission rate     | 10, 20, 50, 125, 250, 500 kbps or 1 Mbps CANopen<br>4800, 9600 or 19200 bps Modbus |
| Number of addresses   | 1...247 Modbus<br>1...127 CANopen  |
| Number of drive       | 127 CANopen<br>31 Modbus   |
| Marking               | CE   |
| Operating position    | Vertical +/- 10 degree   |
| Outer dimension       | 143 x 105 x 150 mm<br>184 x 149 x 145 mm<br>200 x 180 x 144 mm                     |
| Height                | 143 mm   |
| Width                 | 107 mm   |
| Depth                 | 152 mm   |
| Product weight        | 1.8 kg   |

## Environment

|                                       |   |
|---------------------------------------|---|
| Dielectric strength                   | 2040 V DC between earth and power terminals<br>2880 V AC between control and power terminals  |
| Electromagnetic compatibility         | Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 level 4<br>Electrostatic discharge immunity test conforming to IEC 61000-4-2 level 3<br>Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 level 3<br>1.2/50 µs - 8/20 µs surge immunity test conforming to IEC 61000-4-5 level 3 |
| Standards                             | IEC 61800-3<br>IEC 61800-5-1  |
| Product certifications                | CSA<br>C-Tick<br>DNV<br>GOST<br>NOM<br>UL   |
| Pollution degree                      | 2   |
| Protective treatment                  | TC  |
| Vibration resistance                  | 1.5 mm (f = 3...13 Hz) conforming to EN/IEC 60068-2-6<br>1 gn (f = 13...150 Hz) conforming to EN/IEC 60068-2-6  |
| Shock resistance                      | 15 gn for 11 ms conforming to EN/IEC 60068-2-27   |
| Relative humidity                     | 5...95 % without condensation conforming to IEC 60068-2-3<br>5...95 % without dripping water conforming to IEC 60068-2-3  |
| Ambient air temperature for storage   | -25...70 °C   |
| Ambient air temperature for operation | -10...50 °C without derating with protective cover on top of the drive<br>-10...60 °C with derating factor without protective cover on top of the drive   |
| Operating altitude                    | <= 1000 m without derating<br>1000...2000 m with current derating 1 % per 100 m   |

## Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Green Premium product   |
| RoHS (date code: YYWW)   | Compliant - since 0913 - Schneider Electric declaration of conformity<br> <a href="#">Schneider Electric declaration of conformity</a> |

|                                  |  |
|----------------------------------|--|
| REACH                            | Reference not containing SVHC above the threshold<br>Reference not containing SVHC above the threshold               |
| Product environmental profile    | Available<br> Product environmental |
| Product end of life instructions | Available  |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

### ATV312HU15M2 is replaced by:



variable speed drives ATV320U15M2C

variable speed drive ATV320 - 1.5kW - 200...240V - 1 phase - compact

Qty 1

Reason for Substitution: End of life | Substitution date: 03 May 2016